



- Extensive standard equipment
- Infinitely variable spindle speeds up to 3600 rpm

- more rigid and more powerful with 3.75 kW motor
- ISO 40 spindle
- 3 automatic drill feeds
- manual coarse feed for quill, with change-over for manual fine feed
- quill with micrometer depth stop
- reversing switch for forward reverse rotation



Variable throat widths and machining angles



Wide, rigid box ways on Z and Y-axes

- spindle brakes
- infinitely variable speeds
- head swivels $\pm 90^\circ$ to the right and to the left
- TV 1000 table feed in X and Y, infinitely variable with rapid feed
- coolant system
- chip tray
- central lubrication
- pneumatic tool clamping

Specifications

MF 5 VP

Working area	
Table set up area	mm 1.370x250
Table load capacity (max.)	kg 350
Travels	
Travel X-axis	mm 800
Travel Y-axis	mm 390
Travel Z-axis	mm 380
Vertical milling head	
Spindle speed (vertical)	1/min 70 - 3.600
Spindle mount	ISO 40
Quill stroke	mm 127
Feed	
Quill feeds	mm/R (3) 0,04; 0,08; 0,15
Drive capacity	
Motor rating main drive	kW 3,75
Measures and weights	
Overall dimensions (length x width x height)	m 2,54x2,16x2,24
Weight	kg 1.590
Part No.	301217

Standard Equipment

3-axis position indicator, table feed TV 1000 on X- and Y-axis, pneumatic tool clamping, chip tray, coolant system, central lubrication, horizontal guideway cover, operating tools, operator manual

Options

Part No.

• Accessory-Set ISO 40 5-pc.	104596
• Divider ST 130	110960
• HS 125 Hydraulic Machine Vise	125024

For additional options for this machine, visit our website.