



- Extensive standard equipment
- Infinitely variable spindle speeds up to 3600 rpm

- More rigid and more powerful with 5 Hp motor
- ISO 40 spindle
- 3 automatic drill feeds
- Manual coarse feed for quill, with change-over for manual fine feed
- Quill with micrometer depth stop
- Reversing switch for forward reverse rotation



Variable throat widths and machining angles



Wide, rigid box ways on Z and Y-axes

- Spindle brakes
- Infinitely variable speeds
- Head swivels $\pm 90^\circ$ to the right and to the left
- TV 1000 table feed in X and Y, infinitely variable with rapid feed
- Coolant system
- Chip tray
- Central lubrication
- Pneumatic tool clamping

Specifications

MF 5 VP

Working Area		
Table set up area	in	54x10
Table load capacity (max.)	lbs	770
Travels		
Travel X-axis	in	31.5
Travel Y-axis	in	15
Travel Z-axis	in	15
Vertical Milling Head		
Spindle speed (vertical)	rpm	70 - 3,600
Spindle mount		ISO 40
Quill stroke	in	5
Feed		
Quill feeds (3)	in/R	0.002; 0.003; 0.006
Drive Capacity		
Motor rating main drive	Hp	5
Measures and Weights		
Overall dimensions (length x width x height)	in	100x86x89
Weight	lbs	3,498
Part No.		301217

Standard Equipment

3-axis position indicator, table feed TV 1000 on X- and Y-axis, pneumatic tool clamping, chip tray, coolant system, central lubrication, horizontal guideway cover, operating tools, operator manual

Options

Part No.

• Accessory-Set ISO 40 5-pc.	104596
• Divider ST 130	110960
• HS 125 Hydraulic Machine Vise	125024

For additional options for this machine, visit our website.