


SSB 40 F Super • 50 F Super VT

Large drilling capacity and easy handling



See this machine
in action on
YouTube 

- Ideal for drilling, countersinking, reaming and tapping
- heavy construction with thick-walled column
- large drill press table with circumferential coolant groove, height adjustment, and $\pm 45^\circ$ swivel range
- table height adjustment via a powerful motorized drive
- 4 automatic drill feeds with electromagnetic clutch control and automatic shut-off when reaching the limit stop

SSB 50 F Super VT

- Modern operating concept with rugged touchscreen display
- the control system assists the operator with the selection of the correct rpm and feed speed
- the depth stop is set electronically at the display

Standard Equipment

touchscreen, tapping unit, protective shield, LED work lamp, coolant system, operating tools, operator manual


- motorized table height adjustment
- thread cutting function
- automatic quill feed
- infinitely variable speed



Specifications

		SSB 40 F Super	SSB 50 F Super VT
Drilling capacity	mm	40	50
Table set up area	mm	540x440	580x460
Quill stroke	mm	190	200
Spindle nose-to-table surface distance	mm	665	590
Spindle nose-to-foot distance	mm	1.195	1.175
Speed range	1/min	60 - 2.600	50 - 2.200
Spindle mount		MK 4	MK 4
Motor rating main drive	kW	2	2,2
Overall dimensions (length x width x height)	m	1x0,65x2,22	1,15x0,68x2,36
Weight	kg	500	650
Part No.		162335	101673



See this machine
in action on
YouTube 

- heavy cast-iron construction with thick-walled column
- tapping feature
- automatic drill feeds controlled by an electromagnetic clutch
- includes coolant system and work lamp
- table rotates and swivels $\pm 45^\circ$

Standard Equipment

tapping unit, protective shield, LED work lamp, coolant system, operating tools, operator manual

Options

Part No.

• Accessory-Set MT 4 8-pc.	104594
• Vise PB 120	104845
• Clamping Tool Set Deluxe 14/M12	105295

For additional options for this machine, visit our website and search for SSB 32 or 40 Xn (Product Search)

SSB 32 Xn

- head swivels 50° , adjustable height
- digital rpm display



Specifications

		SSB 32 Xn	SSB 40 Xn
Drilling capacity	mm	32	40
Table set up area	mm	500x420	540x440
Quill stroke	mm	160	190
Spindle nose-to-table surface distance	mm	630	610
Table load capacity	kg	100	150
Spindle mount		MK 4	MK 4
Spindle speed	1/min	(12) 125 - 3.030	(12) 75 - 2.020
Quill feeds	mm/R	0,1; 0,2; 0,3	0,12; 0,24; 0,4
Motor rating main drive	kW	1,2	1,5
Overall dimensions (length x width x height)	m	0,84x0,5x1,96	0,95x0,61x2,23
Weight	kg	540	550
Part No.		162332	162339