

Mark Super S • SV

Increased comfort for this compact, versatile powerhouse



See this Machine
in action on
YouTube



- Extensive standard equipment
- Automatic quill feed
- Large travel with TV 1000 table feed
- Multi-function position indicator

Mark Super S • SV

- Motorized cutter head movement and hand-wheel for exact positioning of head
- Hand-wheel for quill micro-feed
- Digital depth indicator for quill travel
- Tapping unit with adjustable rotation reversal for thread cutting
- Hardened gear racks and shafts for quiet operation and long life
- Rigid base with storage room is included
- Infinitely variable feed on X-axis is included



Tapping

Standard Equipment

3-axis position indicator, automatic quill feed, base, table feed TV 1000, drill chuck 1/2", tool-holder bits, operator manual

Options

Part No.

• Clamping Tool Set Deluxe 14/M12	105295
• Mounting Shaft MT 4	108641
• Electronic Edge Tracer	129055

For additional options for this machine, visit our website.

Head swivels $\pm 45^\circ$

- **Mark Super SV - more power and variable speed control for a wider range of applications**
- Two gear steps and premium frequency control technology ensure high torque across the entire speed range for powerful machining
- The selected spindle speed is displayed directly on the control panel

Specifications

		Mark Super S	Mark Super SV
Working Area			
Table dimensions	in	31x9	31x9
Drilling capacity in steel	in	1	1
Guide width	in	7	5
Shaft milling	in	1.26	0.98
Head elevation	in	14	15
Number of table T-slots	positions	3	3
T-slot table (width x spacing)	in	0.55x3.15	0.55x3.15
Travels			
Travel X-axis manual / autom.	in	19 / 22	19 / 22
Travel Y-axis	in	7	7
Vertical Milling Head			
Spindle mount		MT 4	MT 4
Quill stroke	in	5	5
Quill diameter	in	3	3
Spindle nose-to-table distance	in	18	18
Throat	in	10	10
Head swivel range		$\pm 45^\circ$	$\pm 45^\circ$
Speed	rpm	(12) 75-3200	(2) 75-438 / 438-2500
Drive Capacity			
Main motor rating	Hp	2 / 1.5	2
Measures and Weights			
Overall dimensions (length x width x height)	in	50x38x85	49x37x83
Weight	lbs	836	1,056
Part No.		301498	301490